## **Cable Bolts**



## 70T 10 Wire Hollow Cable Bolt



## Features:

- 70 tonne capacity, 10 wires
- Smooth wires for improved strength against shearing
- Standard 31mm diameter and hex drive to suit existing cable bolt accessories i.e. dollies, tensioners and grout lances
- Birdcaged along entire length for maximum load transfer
- · Point anchored with J-LOK "Post-Grout" resin capsules, specifically designed for mixing in larger drill holes
- Top-down grouted using thixotropic grout
- Plated with new higher capacity 12mm thick volcano plates with grout indicator slots. Available in 200x200mm and 300x300mm sizes.
- Plates available for trussing
- Lengths available up to 10m

| Property                               | Typical Value |
|--|---------------|
| Strand diameter (mm)                   | 31            |
| Number wires                           | 12            |
| Wire type                              | smooth        |
| Bulb diameter (mm)                     | 36            |
| Bulb spacing (mm)                      | 500           |
| Steel area (mm <sup>2</sup> )          | 362           |
| Mass (kg/m)                            | 3.5           |
| Typical yield strength (kN)            | 640           |
| Typical Ultimate tensile strength (kN) | 705           |
| Breaking load with barrel & wedge (kN) | 640           |
| Elongation %                           | 5 - 7         |

To suit drill bit 42 - 45mm Conformance Certificates provided for all Civil products

